

SPLIT SYSTEM DX INDOOR UNITS									
SYMBOL			10-AC-01	20-AC-01	20-AC-02	32-AC-01	32-AC-02	80-AC-01	80-AC-02
SERVING			Elec. Room	Elec. Room	Elec. Room	Elec. Room	Elec. Room	Elec. Room	Elec. Room
FAN DATA	SUPPLY AIR	CFM	1102	679	697	1639	1639	1113	1113
	OUTSIDE AIR	CFM	0	0	0	0	0	0	0
	EXTERNAL STATIC PRESS.	IN WG	0.1	0.1	0.1	0.1	0.1	0.1	0.1
DX COOLING DATA	NET CAPACITY	BTU/HR	36000	18000	18000	42000	42000	36000	36000
	NET SENS.	BTU/HR	36000	18000	18000	42000	42000	36000	36000
	ENTERING AIR	DEG. F	DB	89	89	89	89	89	89
	TEMP.	DEG. F	WB	56	56	56	56	56	56
	AMBIENT TEMP.	DEG. F		89	89	89	89	89	89
DIMENSIONS	LENGTH	INCHES	46	36	36	37	37	46	46
	WIDTH	INCHES	12	10	10	63	63	12	12
	HEIGHT	INCHES	14	12	12	9	9	14	14
	MAXIMUM WEIGHT	LBS	53	28	28	86	86	53	53
MANUFACTURER AND MODEL NO.			MITSUBISHI TPKAOAO361KA70A OR EQUAL	MITSUBISHI TPKA0A0181LA00A OR EQUAL	MITSUBISHI TPKA0A0181LA00A OR EQUAL	MITSUBISHI PCAA42KA7 OR EQUAL	MITSUBISHI PCAA42KA7 OR EQUAL	MITSUBISHI TPKAOAO361KA70A OR EQUAL	MITSUBISHI TPKAOAO361KA70A OR EQUAL
APPLICABLE REMARKS:			A	A, B	A, B	A, B, C	A, B, C	A	A
REMARKS: A: AUTO FAN SPEED MODE. B: AIRFLOW DIRECTION CONTROL. C. FILTER STATUS INDICATOR.									

